



ZW-T502H-AS

Wireless Tunner



Voice clarity and comfort for any speaking purpose

Specifications

Model	ZW-T502H-AS
Power Source	AC Adapter : 100 - 240V AC, 50/60Hz
Power Consumption	200mA (13.5V DC, when operating with two tuner modules)
Receiving Frequency	488MHz - 506MHz
Audio Output	Mixed Audio : -0dB(*1), 5kΩ, unbalanced, phone jack Balance A : 0dB(*1), 10kΩ, balanced, XLR-3-32 type connector Balance B : 0dB(*1), 10kΩ, balanced, XLR-3-32 type connector
Antenna	Fixed antenna
Indicator	RF - AF (CH-A), RF -AF (CH-B), LCD-Display
Signal to Noise Ratio	102dB or more (A-weight, balanced output)
Harmonic Distortion	1% or less
Frequency Response	40Hz - 18kHz
Operating Temperature	-10°C to +50°C (14°F to 122°F)
Finish	ABS Resin, black paint
Dimensions	200(W) x 44(H) x 184(D)mm (7.87" x 1.73" x 7.24")
Weight	380g (0.84lb) (without microphone)
Accessory	AC adapter...1, Mic Holder....2, Microphone Handheld...2, Phone Jack Cable...1

(*1) 0dB = 1 V

No	Frequency	Guidance Colors
1	500.40 MHz 488.00 Mhz	Green Yellowish Brown
2	503.60 MHz 491.03 Mhz.	Blue Rose Red
3	505.76 MHz 495.14 Mhz	Orange Bright Yellow

Applications



Conference Meetings



Classroom Teaching

 **TOA**
Smiles for the Public



Like us on Facebook
facebook.com/Toa Indonesia

web: toa.co.id

Specifications are subject to change without notice.